



# "EASY FIT" WATERTIGHT PIPE ENTRY FITTINGS

Only one hole to drill !



- Can be installed in steel - PE and GRP sump walls.
- Tightness is guaranteed with:
  - Cuff bodies with large clip on gaskets,
  - Cuff bodies that are screwed together
  - Flexible boots, tighten by means of stainless or Nylon straps
- Manufactured with high performance materials:
  - Zytel® for the cuff bodies
  - Pellethane® for the boots; All rubber parts are eliminated !
- Approved for all new fuels, ethanol, E85, Bio-diesel.
- Resists UV rays and Ozone.
- Boots available to seal all pipe brands and diameters
- Easy, one man installation thanks to the alignment pins on the cuff bodies
- Double pipe sealing possible when installing a second boot on the outside of the sump
- Boots allow for angled pipe entries exceeding 15°





# "EASY FIT" FITTINGS FOR ALL PIPE BRANDS AND SIZES

## "EASY FIT" CUFFS



### TEF0035 "Easy Fit" cuff body, small size model

- 2 X small cuff bodies
- 2 X flat clip-on gaskets
- 3 X imbedded nuts
- 3 X 2.5" stainless Alien head bolts

### TEF0055 "Easy Fit" cuff body, medium size model

- 2 X medium cuff bodies
- 2 X flat clip-on gaskets
- 4 X imbedded nuts
- 4 X 2.5" stainless Alien head bolts

### TEF0075 "Easy Fit" cuff body, large size model

- 2 X large cuff bodies
- 2 X flat clip-on gaskets
- 5 X imbedded nuts
- 5 X 2.5" stainless Alien head bolts

Use the following tools (hole saw & wrench)



To install	Product code	Description
TEF0035	HS3125	Hole saw 3 1/8" - 80mm
TEF0055	HS5018	Hole saw 5 1/8" - 130mm
TEF0075	HS6058	Hole saw 6 5/8" - 168mm
"Easy Fit" cuffs	ACB034	Alien wrench 3/16, long model

To install "Easy Fit" cuff bodies in curved sump walls

Product Code	Description
TEF35CS	Curved gasket set and bolts for TEF0035 in round sump
TEF55CS	Curved gasket set and bolts for TEF0055 in round sump
TEF75CS	Curved gasket set and bolts for TEF0075 in round sump



# "EASY FIT"

## ALL FLEXIBLE BOOTS IN PELLETHANE®

### "EASY FIT" BOOTS



TRP flexible boot family in Pellethane



TRPC Cap family in Pellethane material

Boots for the small size cuff bodies TEF0035	
TRI3522	Donut for TRP3535 boot, to seal 22mm pipe
TRI3525	Donut for TRP3535 boot, to seal 25mm pipe
TRI3532	Donut for TRP3540 boot, to seal 32mm pipe
TRP3535	Boot for TEF0035 body, to seal 35mm pipe
TRP3540	Boot for TEF0035 body, to seal 40mm pipe
TRPC35	Cap for "Easy fit" TEF0035
Boots for the medium size cuff bodies TEF0055	
TRP5550	Boot for TEF0055 body, to seal 50mm pipe
TRP5563	Boot for TEF0055 body, to seal 63mm pipe
TRP5563A	Boot with airvalve for TEF0055 body, to seal 63mm pipe
TRP5575	Boot for TEF0055 body, to seal 75 mm pipe
TRP5575A	Boot with air valve for TEF0055 body, to seal 75 mm pipe
TR5584	Boot for TEF0055 to seal 90mm PE flexible cable duct pipe
TRP5590	Boot for TEF0055 body, to seal 90 mm pipe
TRP5590A	Boot with air valve for TEF0055 body, to seal 90 mm pipe
TRPD90	Seal for 3,5" secondary duct
TRP5596	Boot for TEF0055 body, to seal 96 mm pipe
TRP5596A	Boot with air valve for TEF0055 body, to seal 96 mm pipe
<b>To seal SP4501 duct externally to the sump wall</b>	
TRP55117	Boot for TEF0055 body, with double Nylon clamp for 4,5" sec. duct
TRP55117S	Boot for TEF0055 body, with double steel clamp for 4,5" sec. duct
TRPD117	Seal for 4,5" secondary duct SP4501
TRPC55	Cap for "Easy Fit" TEF0055
Boots for the large size cuff TEF0075	
TRP7590	Boot for TEF0075 body, to seal 90 mm pipe
TRP7590A	Boot with air valve for TEF0075 body, to seal 90 mm pipe
TRP75110	Boot for TEF0075 body, to seal 110 mm pipe
TRP75110A	Boot with air valve for TEF0075 body, to seal 110 mm pipe
TRP75115	Boot for TEF0075 body, to seal 115 mm pipe
TRP75115A	Boot with air valve for TEF0075 body, to seal 115 mm pipe
TRP75125	Boot for TEF0075 body, to seal 125 mm pipe
<b>To seal SP6001 duct externally to the sump wall</b>	
TRP75145	Boot for TEF0075 body, with double Nylon clamp for 6" sec. duct
TRPD145	Seal for 6" secondary duct SP6001
TRPC75	Cap for TEF0075



# "EASY FIT" FITTINGS RUBBER PARTS ELIMINATED !

The "Easy Fit" pipe entry fittings are built with high quality materials for long term functionality in harsh environments.



The "Easy Fit" cuffs are precision engineered parts, produced by injection moulding using Zytel® a high performance polyamide, based on semi-aromatic nylon co-polymers. It is used in applications such as connectors in wire harnesses, structural automotive components and components for automotive engine-cooling, air intake parts and fuel handling systems. Zytel® retains its tensile strength, rigidity and dimensional stability at elevated ambient temperatures. It offers outstanding chemical resistance to automotive, alcohol doped fuels.

The "Easy Fit" boots are injection moulded using Pellethane®, a high performance polyurethane elastomer. The material offers good low temperature flexibility and impact resistance, as well as an excellent resistance to UV, ozone, fuels, oils and most non-polar solvents. The Pellethane® boots carry UL listing under file nr. MH28727. High quality stainless steel clamps are used to tighten the boots. When installed in high risk areas the boots can eventually be filled with BF4036 urethane filter.



The snap-on gasket on the body cuffs ensures complete tightness with the sump wall.



"Easy Fit" pipe fittings require only one hole to drill in the sump wall!

Each "Easy Fit" cuff comes with a Pellethane® gasket, snapped on the body flange. The outside installed cuff is fitted with hex nuts. The inside installed cuff is fitted with alignment (locating) pins for easy, one man installation. The two cuffs are bolted together with the bolts tighten at max. 60 inch lbs or 0,7 kg.m.